



Industrial Line Co., Ltd.

# Your Own Electricity for Sustainable Profit



## We are Specialized in

- ★ **CHP - COMBINE HEAT AND POWER UNIT**
- ★ **CO-GENERATOR & TRI-GENERATOR**
- ★ **DIESEL GENERATOR**
- ★ **INDUSTRIAL PUMP**
- ★ **HYDRUALIC BREAKER**
- ★ **CUSTOM MACHINERY**
- ★ **AUTOMATION SYSTEM**

## Welcome to **Industrial Line Co.,Ltd.**

"We have been in Energy and Automation business field for more than 15 years.

Our Diesel Generators are supplied by Chicago Pneumatic (CPDG). The units are designed to meet the tough demands of the construction industry. Using proven technology, which draws upon Chicago Pneumatic's history of making generators since the 1930's.

CPDG generators can be relied upon by operators to provide a continuous source of electrical power.

We also serve various quality equipment, i.e. Hydraulic breaker, industrial and mining pump, Biomass Handling system, Waste Handling, Briquette Making System, Shredder, Dryer, Conveyor, Automatic Feeder and else, to provide best solution to efficiently use and handling of waste, energy and fuel in Customer's factories.

ยินดีให้บริการครับ :

โทรเลข : **081-8501516,**  
**081-4466153**

E-mail : [sales@ind-line.com](mailto:sales@ind-line.com)

<https://ind-line.com>



# CP Generator Range

		CPDG60	CPDG85	CPDG105	CPDG120	CPDG150	CPDG200
<b>Electrical data</b>							
Rated frequency	Hz	50	50   60	50   60	50   60	50   60	50   60
Rated voltage	V	400 / 230	400 / 230   480 / 277	400 / 230   480 / 277	400 / 230   480 / 277	400 / 230   480 / 277	400 / 230   480 / 277
Prime power	kVA	61	84   84	104   104	120   120	150   160	200   209
Standby power	kVA	66	91   92	114   115	132   132	164   176	220   230
Power Factor cos phi		0,8	0,8	0,8	0,8	0,8	0,8
<b>Fuel consumption</b>							
Fuel tank capacity (standard / 24-48H / 1000l fuel tank)	l	160 / 520	230 / 680	230 / 680	230 / 680	375 / 950	375 / 950
Fuel consumption @ 100% PRP load	l/h	14	18,5   20	23,4   24,2	27,1   27,3	32,5   35,3	44,1   46,5
Fuel autonomy at full load (standard / 24-48H / 1000l fuel tank)	h	11 / 37	12 / 36   12 / 34	10 / 29   10 / 28	8 / 25   8 / 25	11 / 29   10 / 27	8 / 21   8 / 20
<b>Engine</b>							
Model		John Deere 4045HFU81	John Deere 4045HFU82_A	John Deere 4045HFU82_B	John Deere 4045HFU82_C	John Deere 6068HFU82_A	John Deere 6068HFU82_B
Speed regulation	rpm	1500	1500   1800	1500   1800	1500   1800	1500   1800	1500   1800
Engine exhaust compliance 97/68/CE		EU Stage IIIA	EU Stage IIIA	EU Stage IIIA	EU Stage IIIA	EU Stage IIIA	EU Stage IIIA
<b>Noise level</b>							
Sound power level (LwA)	dB(A)	91	89   92	92   95	95   98	93   96	97   101
Sound pressure level (LpA)	dB(A) at 7 m	65	63   66	66   69	69   72	67   70	71   75
<b>Weight and dimensions</b>							
Length (standard / skid)	mm	2255 / 2300	2900 / 2980	2900 / 2980	2900 / 2980	3265 / 3350	3265 / 3350
Width (standard / skid)	mm	1130	1150	1150	1150	1170	1170
Height (standard / 24H fuel tank)	mm	1615 / 2015	1710 / 2085	1710 / 2085	1710 / 2085	1860 / 2226	1860 / 2226
Weight (standard / 24H fuel tank)	kg	1500 / 1680	1765 / 2000	1855 / 2090	1910 / 2140	2110 / 2400	2210 / 2500



ทางเรามีการรับประกันหลังการขาย และมีศูนย์ซ่อมบำรุงอยู่ในประเทศไทย โดยตรง นอกจากนี้ยังมีสินค้าอื่นๆ ที่ตอบสนองการทำงานได้หลากหลาย



สนใจสามารถติดต่อสอบถามได้ที่  
 081-8501516, 081-4466153  
 หรือ อีเมลสอบถามที่  
 anupap.u@ind-line.com

